



# MATERIAL SAFETY DATA SHEET (MSDS)

## Acclamation All-Systems Floor Finish Floor Finishes



SECTION I ▶ PRODUCT IDENTIFICATION					
<b>Product Name</b>		<b>Product Type</b>		<b>WHMIS Classification</b>	
Acclamation		All-Systems Floor Finish		Not Applicable	
SECTION II ▶ HAZARDOUS INGREDIENTS					
<b>Chemical Name</b>		<b>Cas Registry No.</b>	<b>%</b>	<b>Toxicity</b>	
Not Applicable					
SECTION III ▶ PHYSICAL DATA					
<b>Appearance</b>	<b>Odour</b>	<b>pH</b>	<b>Boiling Point</b>	<b>Specific Gravity</b>	<b>Solubility in Water</b>
White emulsion	Acrylic	8.7	100 °C	1.0	100 %
SECTION IV ▶ FIRE AND EXPLOSION HAZARD DATA					
<b>Flash Point (°C):</b> None			<b>Extinguishing media:</b> Not Applicable		
<b>Special fire fighting procedures:</b> None					
<b>Unusual fire and explosion hazards:</b> None					
SECTION V ▶ TOXICOLOGICAL PROPERTIES					
<b>HAZARD RATING:</b> Health = 1 Flammability = 0 Reactivity = 0					<b>Rating System</b> 0 = Insignificant 1 = Slight 2 = Moderate 3 = High 4 = Extreme
<b>Swallowing:</b> Slightly Toxic.					
<b>Inhalation:</b> Not Applicable					
<b>Skin Absorption:</b> Not Applicable					
<b>Skin Contact:</b> Slight Irritant					
<b>Eye Contact:</b> Slight Irritant					
<b>Special Warning:</b> None					
SECTION VI ▶ FIRST AID MEASURES					
<b>Ingestion:</b> Drink 3-4 glasses of milk or water.					
<b>Inhalation:</b> Not Applicable					
<b>Skin:</b> Flush with water.					
<b>Eyes:</b> Flush with water. If irritation persists, call a physician.					
SECTION VII ▶ REACTIVITY DATA					
<b>Stable:</b> Yes					
<b>Conditions to avoid:</b> None					
<b>Incompatibility with other materials:</b> None					
<b>Hazardous decomposition products:</b> None					
<b>Hazardous polymerization:</b> Will not occur.					
SECTION VIII ▶ PREVENTIVE MEASURES					
<b>Hand protection:</b> No					
<b>Eye protection:</b> No					
<b>Ventilation:</b> General					
<b>Respiratory protection:</b> None					
<b>Other protective equipment:</b> None					
<b>Steps to be taken in case material is released or spilled:</b> Mop up spillage. Rinse spill area with water and allow to dry.					
<b>Waste disposal method:</b> Flush with water into waste systems in accordance with municipal, provincial and federal regulations.					
<b>Precautions to be taken in handling and storage:</b> Normal handling processes. Inside storage at 4-40 °C recommended.					
<b>Other precautions:</b> Follow label use instructions.					
<b>UN:</b> Not Applicable		<b>TDG Class:</b> None		<b>Packing Group:</b> Not Applicable	
<b>TDG Emergency Telephone Number:</b> 613-996-666 (COLLECT)					
SECTION IX ▶ PREPERATION DATA					
<b>Prepared by:</b> D.R. Dunlop			<b>Last updated:</b> October 15, 2009		
<b>Location:</b> Dustbane Products Limited, 25 Pickering Place, Ottawa, Ontario, K1G 5P4 – 613-745-6861					

# Acclamation

## All-Systems Floor Finish

"Fast drying formula... Developed for use in high profile areas where the ultimate "wet look" gloss and durability are desired."

### FEATURES AND BENEFITS

**Environmentally Friendly:** A.P.E. free

**Fast drying:** Will dry in as few as 15 minutes.

**High solids:** Excellent durability; resists scuff, scratches, heel marks, etc.

**Slip resistant:** Produces a safe, slip-free surface.

**Easy to apply:** Excellent levelling and gloss; non streaking; no mop drag.

**Easy to remove:** Readily removed using conventional strippers.

### WHERE TO USE

Should be used to protect and enhance the appearance of high profile area floors such as showrooms, foyers, reception areas, lobbies and other areas in shopping malls, airports, hospitals, nursing homes, universities, theatres and commercial buildings. May be applied to all resilient and non-resilient floors except for unsealed wood and cork.

### HOW TO USE

**PREPARATION:** Before you initial application, use FORMULA-1 or CHAMPION to strip the floor of any old finish. Rinse thoroughly with potable water, allow to dry then seal floor. (If stripping is not possible then deep scrub using a Dustbane neutral detergent.

**APPLICATION:** Using a clean mop and bucket, apply 1-3 coats of ACCLAMATION (depending upon porosity of the floor), allowing approximately 15 minutes drying time between coats.

**MAINTENANCE:** Dust and/or wet mop daily. Spray buff as needed. For best results, after damp mopping with a neutral floor detergent, apply a Dustbane recommended restorer or ACCLAMATION diluted at 1:4, let dry for 15-30 minutes then burnish the floor.

### SPECIFICATIONS

**Type:** Acrylic styrene copolymer

**Appearance:** White emulsion

**Fragrance:** Acrylic

**Viscosity:** As water

**pH:** 8.7

**Slip Resistance:** 0.5 min (ASTM D-2047)

**Freeze-Thaw Stability:** Passes 3 cycle

**Dry Time:** 15 minutes

**Non-volatile %:** 20.0

**WHMIS:** No

**TDG:** No