



MATERIAL SAFETY DATA SHEET (MSDS)

Cross-Link 2000

Spray Buff Maintainer

Floor Finishes



SECTION I ▶ PRODUCT IDENTIFICATION					
Product Name		Product Type		WHMIS Classification	
Cross-Link 2000		Spray Buff Maintainer		D2B	
SECTION II ▶ HAZARDOUS INGREDIENTS					
Chemical Name		Cas Registry No.	%	Toxicity	
d-limonene		5989-27-5	3-7	LD50ORAL(RAT) 4400 mg/kg	
Diethylene glycol ethyl ether		111-90-0	1-5	LD50ORAL(RAT) 5500 g/kg	
SECTION III ▶ PHYSICAL DATA					
Appearance	Odour	pH	Boiling Point	Specific Gravity	Solubility in Water
White emulsion	Scented	8.7	100 °C	1.0	100 %
SECTION IV ▶ FIRE AND EXPLOSION HAZARD DATA					
Flash Point (°C): None			Extinguishing media: Not Applicable		
Special fire fighting procedures: None					
Unusual fire and explosion hazards: None					
SECTION V ▶ TOXICOLOGICAL PROPERTIES					
HAZARD RATING: Health = 2 Flammability = 1 Reactivity = 0					Rating System 0 = Insignificant 1 = Slight 2 = Moderate 3 = High 4 = Extreme
Swallowing: Slightly Toxic.					
Inhalation: Not Applicable					
Skin Absorption: Not Applicable					
Skin Contact: Irritant					
Eye Contact: Irritant					
Special Warning: None					
SECTION VI ▶ FIRST AID MEASURES					
Ingestion: Do not induce vomiting Drink 3-4 glasses of milk or water. Call a physician.					
Inhalation: Not Applicable					
Skin: Flush with water. If irritation persists, call a physician.					
Eyes: Flush with water for 15 minutes. If irritation persists, call a physician.					
SECTION VII ▶ REACTIVITY DATA					
Stable: Yes					
Conditions to avoid: Sources of ignition					
Incompatibility with other materials: Strong oxidizing agents.					
Hazardous decomposition products: None					
Hazardous polymerization: Will not occur.					
SECTION VIII ▶ PREVENTIVE MEASURES					
Hand protection: No					
Eye protection: No					
Ventilation: General					
Respiratory protection: No					
Other protective equipment: None					
Steps to be taken in case material is released or spilled: Mop up spillage. Rinse spill area with water and allow to dry.					
Waste disposal method: Flush with water into waste systems in accordance with municipal, provincial and federal regulations.					
Precautions to be taken in handling and storage: Normal handling processes. Inside storage at 4-40 °C recommended.					
Other precautions: Follow label use instructions.					
UN: Not Applicable		TDG Class: None		Packing Group: Not Applicable	
TDG Emergency Telephone Number: 613-996-6666 (COLLECT)					
SECTION IX ▶ PREPERATION DATA					
Prepared by: D.R. Dunlop			Last updated: December 1, 2009		
Location: Dustbane Products Limited, 25 Pickering Place, Ottawa, Ontario, K1G 5P4 – 613-745-6861					

Cross-Link 2000

Spray Buff Maintainer

"A newly formulated spray buff solution used to repair your floor and maintain its high appearance between refinishing."

FEATURES AND BENEFITS

Polymer technology – A.P.E. free., zinc free

Easy application - simply spray on and buff

Easy recoating - does not harm or damage floor for easy re-application of finish

Slip resistant - will not affect slip resistance of floor finish

Maintains gloss level – removes scratches and heel marks

Natural citrus solvent – cuts through black heel marks with ease

WHERE TO USE

Use in heavy traffic areas such as hospital corridors, school classrooms, hallways, lobbies, supermarket aisles, malls, public office buildings and places where there is heavy foot traffic and where an outstanding appearance is desired.

HOW TO USE

Damp mop or auto scrub the floor with a neutral detergent. Spray buff whole areas using CROSS-LINK 2000 A.P.E. FREE with a RED PAD. Do not let spray buff dry on the floor. Spray a light mist to avoid quick pad overload.

SPECIFICATIONS

Type: emulsion

Appearance : white liquid

Fragrance : citrus

Viscosity : as water

pH : 8.7

Slip Resistance : 0.5 min (ASTM D-2047)

Dry Time : N/A

WHMIS : yes

TDG : no