



MATERIAL SAFETY DATA SHEET (MSDS)

Restore

Ultra High Speed Floor Maintainer

Floor Finishes



SECTION I ▶ PRODUCT IDENTIFICATION					
Product Name		Product Type		WHMIS Classification	
Restore		Ultra High Speed Floor Maintainer		Not Applicable	
SECTION II ▶ HAZARDOUS INGREDIENTS					
Chemical Name		Cas Registry No.	%	Toxicity	
Not Applicable					
SECTION III ▶ PHYSICAL DATA					
Appearance	Odour	pH	Boiling Point	Specific Gravity	Solubility in Water
White Liquid	Acrylic	9.7	100 °C	1.0	100 %
SECTION IV ▶ FIRE AND EXPLOSION HAZARD DATA					
Flash Point (°C): None			Extinguishing media: Not Applicable		
Special fire fighting procedures: None					
Unusual fire and explosion hazards: None					
SECTION V ▶ TOXICOLOGICAL PROPERTIES					
HAZARD RATING: Health = 1 Flammability = 0 Reactivity = 0					Rating System 0 = Insignificant 1 = Slight 2 = Moderate 3 = High 4 = Extreme
Swallowing: Slightly Toxic.					
Inhalation: Not Applicable					
Skin Absorption: Not Applicable					
Skin Contact: Slight Irritant					
Eye Contact: Slight Irritant					
Special Warning: None					
SECTION VI ▶ FIRST AID MEASURES					
Ingestion: Drink 3-4 glasses of milk or water.					
Inhalation: Not Applicable					
Skin: Flush with water.					
Eyes: Flush with water. If irritation persists, call a physician.					
SECTION VII ▶ REACTIVITY DATA					
Stable: Yes					
Conditions to avoid: None					
Incompatibility with other materials: None					
Hazardous decomposition products: None					
Hazardous polymerization: Will not occur.					
SECTION VIII ▶ PREVENTIVE MEASURES					
Hand protection: No					
Eye protection: No					
Ventilation: General					
Respiratory protection: None					
Other protective equipment: None					
Steps to be taken in case material is released or spilled: Mop up spillage. Rinse spill area with water and allow to dry.					
Waste disposal method: Flush with water into waste systems in accordance with municipal, provincial and federal regulations.					
Precautions to be taken in handling and storage: Normal handling processes. Inside storage at 4-40 °C recommended.					
Other precautions: Follow label use instructions.					
UN: Not Applicable		TDG Class: None		Packing Group: Not Applicable	
TDG Emergency Telephone Number: 613-996-6666 (COLLECT)					
SECTION IX ▶ PREPERATION DATA					
Prepared by: D.R. Dunlop			Last updated: November 1, 2009		
Location: Dustbane Products Limited, 25 Pickering Place, Ottawa, Ontario, K1G 5P4 – 613-745-6861					

Restore

Ultra High Speed Floor Maintainer

"A triple action floor maintainer for ultra high speed maintenance programs which cleans and restores while maintaining an exceptional appearance. Can be used as a mop-on finish or in automatic scrubbers."

FEATURES AND BENEFITS

Environmentally friendly – A.P.E. free

Maintains "Wet-Look" – restores high level of appearance on burnished floors

Cleans while it shines – built in detergents clean floors while the shine is restored

Easy to apply – no special equipment or applicators are required

Slip resistant – maintains slip resistance of floor finish

WHERE TO USE

Use to rejuvenate UHS floor finishes. Cleans while polishing and removing scuff marks, etc. Extends the life of the floor finish especially when used in high traffic areas. May be applied to all resilient and non-resilient floors except for unsealed wood and cork.

HOW TO USE

Remove any surface dirt or dust with a treated mop and clean floor with a neutral detergent.

Mop-On Application: dilute 1:20

Apply RESTORE with a clean mop daily to enhance the gloss and preserve the finish in traffic areas.

Automatic Scrubber Application: dilute 1:20

Fill scrubber reservoir. Regulate the flow of the RESTORE solution at a low, steady rate. Apply just enough pressure on the pad assembly to touch the surface of the floor. The rejuvenated area will be ready for traffic in minutes after cleaning. Rinse the automatic scrubber tank thoroughly with water after use to prevent film build-up.

Dry Burnishing: dilute 1:4

Routinely, apply RESTORE with a clean mop. Allow the solution to dry for 30 minutes before dry burnishing with Dustbane UHS buffing pad.

SPECIFICATIONS

Type : acrylic emulsion

Appearance : white liquid

Fragrance : acrylic

Viscosity : as water

pH : 9.7

Slip Resistance : 0.5 min (ASTM D-2047)

Freeze-thaw stability : passes 3 cycles

Dry Time : 15-30 mins.

WHMIS: no

TDG : no