

Acclamation

All Systems Floor Finish



Applications:

Preparation: Before your initial application, the floor must be stripped of any old finish, rinsed thoroughly with potable water and allowed to dry. Sealing the floor is recommended prior to applying a floor finish.

Application: Using a clean mop and bucket, apply 1-3 coats (depending on the porosity of the floor) allowing the floor to completely dry between coats, at least 15 minutes or more.

Maintenance: Sweep or dry mop frequently. Wet mop or auto-scrub periodically with a properly diluted neutral detergent. Scrub and recoat worn traffic areas as required. Spray buff as needed. Burnishing daily is highly recommended but not imperative.

Benefits:

- Exceptional gloss
- Wear and scuff resistant
- Excellent slip resistance
- Detergent resistant
- Protects both resilient and non-resilient floors


Codes:

- **Product Codes:** 52060 (5 L)
52061 (20 L)
- **UPC:** 0 56069 52060 7 (5 L)
0 56069 52061 7 (20 L)

Specifications:

Colour	White
DIN	No
Odour	Acrylic
pH	8.2 - 8.8
Coverage	186 m ² (2000 ft ²) to 297 m ² (3200 ft ²) (5 L)
Number of Coats	1 - 3
Drying Time	15 minutes
Refractive Index	23.9 - 24.3
Non-Volatile Solids	20%
VOC Content	52 g/L
COF	0.5
Gloss Rating	87 - 89%
Viscosity	Not determined
Solvent	No
Phosphates	No
WHMIS	Yes
ECOLOGO®	No
Food Safe	No
Kosher	Yes
Shelf Life	Up to 3 years after manufacturing

Available Formats:



5 L

20 L

Packaging:

- Bottle:** 6.1" x 6.1" x 12.6" (15.5 x 15.5 x 31.9 cm)
12.25 lbs (5.56 kg)
- Pail:** 12" x 12" x 16" (30.5 x 30.5 x 41 cm)
48 lbs (22 kg)
- Box (5 L):** 12.4" x 12.4" x 13"
49 lbs (22.23 kg)
4 per case

