

EnviroFlex

Proportioning System



Applications:

Proper cleaning starts with proper dilution. This system can be configured with 2 (1 GPM)+2 (3.5 GPM) or 3 (1 GPM)+1 (3.5 GPM), allowing product and application flexibility and allowing you to customize the system to your needs.

Benefits:

- Combination of low and high low rates, using separate 1 GPM or 3.5 GPM
- AccuPro Technology provides consistent dispenses the precise amount of chemicals regardless of water pressure
- Uses less space than dispenser + separate chemicals
- High-quality dispenser stands up to daily wear and tear
- Easy, tool-free maintenance
- Chemically resistant select valves

Specifications:

Colour	Blue/White
System	Quad Dispensing
Maximum Temperature	120 °F
Flow Rates	1 - 3.5 GPM
Minimum Pressure	25 psi
Maximum Pressure	85 psi
Available Dilution Rates	Up to 17
Back Flow Preventer	E-Gap
Certification	N/A

Codes:

- **Product Code:** HSP7983 (3+1)
HSP7984 (2+2)

Packaging:

Dispenser: 6.25" x 7" x 13" (16 x 18 x 33 cm)
4 lbs (1.8 kg)

Box: 6.325" x 15.25" x 18" (16 x 39 x 46 cm)
5 lbs (2.27 kg)
1 per case

