

Foundation

Floor Sealer



Applications:

Designed to give total sealer protection to resilient (except unsealed wood) and non-resilient (except magnesite) floors. Apply using a clean mop or sprayer, allowing 30-60 minutes between applications. Two or three coats are recommended.

Benefits:

- Ideal as a base coat for floor finishes
- Excellent slip resistance
- Detergent resistant
- Safe for all types of flooring
- Ideal for dust control for concrete floors
- Protects flooring
- Solvent free – no harmful vapours

Codes:

- **Product Code:** 53777 (4 L)
53779 (20 L)
- **UPC:** 0 56069 53777 3 (4 L)
0 56069 53779 7 (20 L)

Specifications:

Colour	White
DIN	No
Odour	Acrylic
pH	8.4 - 8.8
Viscosity	Not determined
Solvent	No
Phosphates	No
WHMIS	Yes
ECOLOGO	Yes
Food Safe	No
Kosher	Yes
Shelf Life	Up to 3 years after manufacturing
Coverage	150 m ² (1600 ft ²) to 232 m ² (2500 ft ²) (4 L)
Number of Coats	2 - 3
Drying Time	30 - 60 minutes
Solid Content	16%
COF	0.7
Shelf Life	Up to 3 years after manufacturing



Available Formats:



Packaging:

- Bottle:** 5.8" x 5.8" x 12.3" (14.7 x 14.7 x 31 cm)
10 lbs (4.5 kg)
- Pail:** 12" x 12" x 16" (30.5 x 30.5 x 41 cm)
48 lbs (22 kg)
- Box:** 11.6" x 11.6" x 12.9"
40 lbs (18 kg)
4 per case