

Gard Floor Sealer



Applications:

Preparation:

Before your initial application, the floor must be stripped of any old finish, rinsed thoroughly with potable water and allowed to dry.

Application:

Using a clean mop or sprayer, apply 2-3 coats (depending on the porosity of the floor) allowing the floor to completely dry between coats, at least 30-60 minutes or more depending on humidity condition.

Benefits:

- Ideal as a base coat for floor finishes
- The solids fill and seal pores as they harden
- Provides a smoother floor surface
- Excellent slip resistance
- Detergent resistant
- High durability for long-lasting protection
- Protects both resilient and non-resilient floors

Codes:


- **Product Code:** 53784 (5 L)
53785 (20 L)
- **UPC:** 0 56069 53784 1 (5 L)
0 56069 53785 8 (20 L)



Specifications:

Colour	White
DIN	No
Odour	Acrylic
pH	8.4 - 8.8
Viscosity	Not determined
Solvent	No
Phosphates	No
WHMIS	Yes
ECOLOGO	No
Food Safe	No
Kosher	Yes
Shelf Life	Up to 3 years after manufacturing
Coverage	170 m ² (1830 ft ²) to 280 m ² (3014 ft ²) (5 L)
Number of Coats	2 - 3
Drying Time	30 - 60 minutes
Solid Content	15%
COF	0.7
Shelf Life	Up to 3 years after manufacturing

Available Formats:



5 L

20 L

Packaging:

- Bottle:** 6.1" x 6.1" x 12.6" (15.5 x 15.5 x 31.9 cm)
12.25 lbs (5.56 kg)
- Pail:** 12" x 12" x 16" (30.5 x 30.5 x 41 cm)
48 lbs (22 kg)
- Box (5 L):** 12.4" x 12.4" x 13"
49 lbs (22.23 kg)
4 per case