

Glacier

High Solids Floor Finish



Applications:

- Preparation:** Before your initial application, the floor must be stripped of any old finish, rinsed thoroughly with potable water and allowed to dry. Sealing the floor is recommended prior to applying a floor finish.
- Application:** Using a clean mop and bucket, apply 1-3 coats (depending on the porosity of the floor) allowing the floor to completely dry between coats, at least 45 minutes or more.
- Maintenance:** Sweep or dry mop frequently. Wet mop or auto-scrub periodically with a properly diluted neutral detergent. Scrub and recoat worn traffic areas as required. Spray buff as needed.

Benefits:

- Exceptional gloss
- Ideal for low maintenance programs
- Protects from stains, scuffs, and scratches
- Labour saving and detergent resistant
- Protects both resilient and non-resilient floors

Codes:

- **Product codes:** 53935 (5 L)
53936 (20 L)
- **UPC:** 0 56069 53935 7 (5 L)
0 56069 53936 4 (20 L)

Specifications:

Colour	White
DIN	No
Odour	Acrylic
pH	8.4 - 8.8
Viscosity	Not determined
Solvent	No
Phosphates	No
WHMIS	Yes
ECOLOGO	No
Food Safe	No
Kosher	Yes
Coverage	186 m ² (2000 ft ²) to 297 m ² (3200 ft ²) (5 L)
Number of Coats	1 - 3
Drying Time	45 minutes
Refractive Index	31.7 - 32.1
Non-Volatile Solids	25%
COF	0.5
Gloss Rating	88%
Shelf Life	Up to 3 years after manufacturing



Available Formats:



5 L



20 L

Packaging:

- Bottle:** 6.1" x 6.1" x 12.6" (15.5 x 15.5 x 31.9 cm)
12.25 lbs (5.56 kg)
- Pail:** 12" x 12" x 16" (30.5 x 30.5 x 41 cm)
48 lbs (22 kg)
- Box (5 L):** 12.4" x 12.4" x 13"
49 lbs (22.23 kg)
4 per case