Gran-Prix XL All Systems Floor Finish



Applications:

Preparation: Before your initial application, the floor must be stripped of any old finish, rinsed thoroughly with potable water

and allowed to dry. Sealing the floor is recommended prior to applying a floor finish.

Application: Using a clean mop and bucket, apply 1-3 coats (depending on the porosity of the floor) allowing the floor

to completely dry between coats, at least 30 minutes or more.

Maintenance: Sweep or dry mop frequently. Wet mop or auto-scrub periodically with a properly diluted neutral detergent. Scrub

and recoat worn traffic areas as required. Spray buff as needed. Remove any surface dirt and dust with a treated mop. Wet mop or auto-scrub periodically with a neutral detergent. Scrub and recoat worn traffic areas as required.

Benefits:

• Exceptional gloss

• Ideal for low maintenance programs

• Protects from stains, scuffs, and scratches

· Labour saving and detergent resistant

• Protects both resilient and non-resilient floors

Codes:

• **Product codes:** 52020 (5 L)

52021 (20 L)

• UPC: 0 56069 52020 4 (5 L) 0 56069 52021 8 (20 L)



Specifications:

Colour	White
DIN	No
Odour	Acrylic
рН	8.2 - 8.7
Viscosity	Not determined
Solvent	No
Phosphates	No
WHMIS	Yes
ECOLOGO	No
Food Safe	No
Kosher	Yes
Coverage	186 m ² (2000 ft ²) to 297 m ² (3200 ft ²) (5 L)
Number of Coats	1 - 3
Drying Time	30 minutes
Refractive Index	25.7 - 26.2
Non-Volatile Solids	19%
COF	0.6
Gloss Rating	85%
Shelf Life	Up to 3 years after manufacturing

Available Formats:



Packaging:

Bottle: 6.1" x 6.1" x 12.6" (15.5 x 15.5 x 31.9 cm)

12.25 lbs (5.56 kg)

Pail: 12" x 12" x 16" (30.5 x 30.5 x 41 cm)

48 lbs (22 kg)

Box (5 L): 12.4" x 12.4" x 13"

49 lbs (22.23 kg) 4 per case