

Polytec

Urethane-Based Sealer



Applications:

Preparation:

Floors must be thoroughly clean and dry, free of all dirt, oil, grease and wax. Do not apply in humid conditions or at a temperature below 10°C (50°F). Concrete floors should be acid etched if less than 6 months old. This will produce a better bonding surface.

Application:

Apply using a lambswool applicator, string mop, roller or similar apparatus. Use light even strokes, rubbing in and spreading to avoid build-up of a heavy film. Subsequent coats must only be applied over a previous coat that is thoroughly dry and hard. Good practice procedures are generally to allow an overnight dry before a subsequent application is made.

Maintenance:

Maintain by dust mopping with a treated mop and damp mopping with a neutral detergent. Worn areas may be repaired by "feathering" in a new coat of Polytec.

Benefits:

- Excellent colour clarity
- The solids fill and seal pores as they harden
- Provides a smoother floor surface
- Excellent slip resistance
- Detergent resistant
- High durability for long-lasting protection

Codes:

- **Product Code:** 53512 (20 L)
- **UPC:** 0 56069 53512 0 (20 L)



20 L

Specifications:

Colour	Clear
DIN	No
Odour	Solvent
pH	Not applicable
Viscosity	Not determined
Solvent	Yes
Phosphates	No
WHMIS	Yes
ECOLOGO	No
Food Safe	No
Kosher	Yes
Shelf Life	Up to 3 years after manufacturing
Coverage	33 m ² (360 ft ²) to 46 m ² (500 ft ²) (5 L)
Number of Coats	1 - 2
Drying Time	Overnight
Shelf Life	Up to 3 years after manufacturing

Available Format:

Packaging:

Pail: 12" x 12" x 16" (30.5 x 30.5 x 41 cm)
48 lbs (22 kg)