Integra-D

Integra Series





Floor Preparation Machines

Chemical-Free Floor Scrubbing

Gives operators the ability to remove multiple layers of finish, without using chemicals.

Superior Dust Pickup

Used in combination with the Fast Track Kit, it's ingeniously designed to pick up 80% of grinding residue at the source and on the first pass. Practically dustless scrubbing and stripping, with less clean up, to increase your productivity.

Innovative

The uniquely designed floating head completely isolates any vibration through the handle – eliminating directional drift and making steering effortless. Incorporating 4 and 8 independent isolators, the Integra-D can run hour after hour with no operator complaints. The sliding weights and removable handle make for easy transportation.

Specifications		20″	28"
Model Number		19936	19937
Productivity	VCT	2500 ft²/hr (232 m²/hr)	3375 ft²/hr (314 m²/hr)
	Gym	5000 ft²/hr (465 m²/hr)	7500 ft²/h (697 m²/hr)
Scrubbing Width		14" x 20" (36 cm x 51 cm)	14" x 28" (36 cm x 71 cm)
Scrubbing Pressure		0.59 psi	0.60 psi
Motor Power		1.5 hp	1.5 hp
Oscillations		3450 rpm	3450 rpm
Voltage		120 V	120 V
Removable Handle		Yes	Yes
Adjustable Handle		Yes	Yes
Weight (Assembled)		165 lbs (75 kg)	235 lbs (107 kg)
Maximum Weight Capacity		Scalable to application	Scalable to application
Removable Weights		Yes (Sliding)	Yes (Sliding)
Weights		2 x 6.7 lbs (3.0 kg) / 6 x 10.1 lbs (4.6 kg)	2 x 10.6 lbs (4.8 kg) / 6 x 17.7 lbs (8.0 kg)
Frame		11 gauge steel	11 gauge steel
Axle		3/4 mechanical tube + 1/3 solid axle	3/4 mechanical tube + 1/3 solid axle
Wheels		(2) 2" x 6" (2 x 15 cm)	(2) 2" x 6" (2 x 15 cm)
Isolators		4	8
Power Cord		50′ (15 m) / 14 gauge	50' (15 m) / 14 gauge
Unit Size (L x W x H)		14.5" x 20.5" x 49" (37 x 52 x 124 cm)	14.5" x 28.5" x 49" (37 x 72 x 124 cm)
Noise Level		60 dB	60 dB
Approval(s)		QPS	QPS